



COR 2000

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 U_w from 1.8 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **30 mm.**
 Maximum acoustic insulation: **Rw = 39 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000): **Class 4**
 Water tightness (UNE-EN 12208:2000): **Class 9A**
 Wind resistance (UNE-EN 12210:2000): **Class C5**

Reference test window 1.20 x 1.18 m. 2 sashes.

SECTIONS	Frame 45 mm Sash 53 mm
PROFILE THICKNESS	Window 1.5 mm Door 1.7 mm
MAXIMUM DIMENSIONS	Width (L) = 1,500 mm Height (H) = 2,400 mm
MAXIMUM WEIGHT/SASH	120 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns
	Wood effect powder coating According to Qualideco standard
	Anodized According to Ewma Euras Standard Class 15 Optionally Class 20 and 25

HERRAJE	Optionally concealed hinges Optionally security hardware
---------	---

EXTRUSION ALLOY
6063 T-5

GASKETS
EPDM triple gasket

OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and parallel-tilt
OUTWARDS	Side hung, top hung and pivoting on horizontal or vertical axis

