



COR 2300

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 2.0 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **26 mm.**

Maximum acoustic insulation: **Rw = 39 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class 9A

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.105 x 1.210 m. 2 sashes.

SECTIONS	Frame 40 mm Sash 48 mm
PROFILE THICKNESS	Window 1.3 mm Door 1.4 mm
MAXIMUM DIMENSIONS	Width (L) = 1,500 mm Height (H) = 2,400 mm
MAXIMUM WEIGHT/SASH	120 Kg.

Please consult maximum dimensions according to types.

FINISHES	<p>Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns</p> <p>Wood effect powder coating According to Qualideco standard</p> <p>Anodized According to Ewma Euras Standard Class 15 Optionally Class 20 and 25</p>
----------	---

HERRAJE	<p>Optionally concealed hinges</p> <p>Optionally security hardware</p>
---------	--

EXTRUSION ALLOY	6063 T-5
-----------------	----------

GASKETS	EPDM triple gasket
---------	--------------------

OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and parallel-tilt
OUTWARDS	Side hung, top hung and pivoting on horizontal or vertical axis

