

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.0 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **41 mm.**

Maximum acoustic insulation: **Rw = 46 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class E1200**

Wind resistance (UNE-EN 12210:2000):

**Class C5**

Reference test window 1.20 x 1.20 m. 2 sashes.

SECTIONS	Frame 54 mm Sash 63 mm
PROFILE THICKNESS	Window 1.5 mm Balcony 1.7 mm
MAXIMUM DIMENSIONS	Width (L) = 1,500 mm Height (H) = 2,400 mm
MAXIMUM WEIGHT/SASH	120 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns
	Wood effect powder coating According to Qualideco standard
	Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25
	Optionally bicoloured

EXTRUSION ALLOY
6063 T-5

POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass: 24 mm

GASKETS
EPDM triple gasket

FOAMS
Perimeter polyolefin foam in glazing rebate zone

OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and paralel tilt
OUTWARDS	Side hung and top hung

