

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 0.9 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **55 mm.**

Maximum acoustic insulation: **Rw = 46 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1500

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.23 x 1.48 m. 2 sashes.

SECTIONS	Frame 70 mm Sash 78 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.5 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : Frame 35 mm Sash 30 mm
MAXIMUM DIMENSIONS	Width (L) = 1,500 mm Height (H) = 2,600 mm	GASKETS	EPDM triple gasket
MAXIMUM WEIGHT/SASH	Aluminium hardware 120 Kg PVC hardware 100 Kg	FOAMS	Perimeter polyolefin foam in glazing rebate zone
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns	OPENING POSIBILITIES	INWARDS Side hung, turn&tilt, tilt and parallel-tilt. Optionally turn&tilt with threshold for disabled
	Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		

Please consult maximum dimensions according to types.

