

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 U_w from 1.2 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: Outwards sash **22 mm** / Inwards sash: **30 mm**
 Maximum acoustic insulation: **Rw = 50 dB**.

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1650

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.23 x 1.48 m. 2 sashes

SECTIONS	Frame 122 mm Sash 121 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.6 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : Frame 35 mm Sash 20 mm
MAXIMUM DIMENSIONS	Width (L) = 1,100 mm Height (H) = 2,200 mm	GASKETS	EPDM quadruple gasket
MAXIMUM WEIGHT/SASH	150 Kg.	OPENING POSIBILITIES	INWARDS Side hung, turn&tilt. 1 and 2 sashes.
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		

Please consult maximum dimensions according to types.

